

型号	尺寸 (mm)				基本额定载荷 (N)		疲劳极限 载荷 (N)	极限速度 (r/min)	速度参数 (r/min)	重量
	d	D	B(or)T	Rmin	Cr	Cor	Cur	Ng	Nb	(kg)
NCF3004CV	20	42	16	0,6	28,1	28,5	3,1	8500	10000	0,11
NCF3005CV	25	47	16	0,6	31,9	35,5	3,8	7000	9000	0,12
NJG2305VH	25	62	24	1,1	68,2	68	8,5	4500	5600	0,38
NCF3006CV	30	55	19	1	39,6	44	5	6000	7500	0,20
NJG2306VH	30	72	27	1,1	84,2	86,5	11	4000	4800	0,56
NCF3007CV	35	62	20	1	48,4	56	6,55	5300	6700	0,26
NJG2307VH	35	80	31	1,5	108	114	14,3	3400	4300	0,75
NCF3008CV	40	68	21	1	57,2	69,5	8,15	4800	6000	0,31
NJG2308VH	40	90	33	1,5	145	156	20	3000	3600	1,00
NCF3009CV	45	75	23	1	60,5	78	9,15	4300	5300	0,40
NJG2309VH	45	100	36	1,5	172	196	25,5	2800	3400	1,45
NCF3010CV	50	80	23	1	76,5	98	11,8	4000	5000	0,43
NCF3011CV	55	90	26	1,1	105	140	17,3	3400	4300	0,64
NJG2311VH	55	120	43	2	233	260	33,5	2200	2800	2,30
NCF2912CV	60	85	16	1	55	80	9,15	3600	4500	0,29
NCF3012CV	60	95	26	1,1	106	146	18,3	3400	4000	0,69
NCF2913CV	65	90	16	1	58,3	88	10,2	3200	4000	0,31
NCF3013CV	65	100	26	1,1	112	163	20	3000	3800	0,73
NJG2313VH	65	140	48	2,1	303	360	46,5	1900	2400	3,55
NCF2914CV	70	100	19	1	76,5	116	13,7	3000	3800	0,49
NCF3014CV	70	110	30	1,1	128	173	22,4	2800	3600	1,02
NJG2314VH	70	150	51	2,1	336	400	50	1800	2200	4,40
NCF2915CV	75	105	19	1	79,2	125	14,6	2800	3600	0,52
NCF3015CV	75	115	30	1,1	134	190	24,5	2600	3200	1,06
NJG2315VH	75	160	55	2,1	396	480	60	1600	2000	5,35
NCF2916CV	80	110	19	1	80,9	132	15,6	2600	3400	0,55

NCF3016CV	80	125	34	1, 1	165	228	29	2400	3000	1, 43
NJG2316VH	80	170	58	2, 1	457	570	71	1500	1900	6, 40
NCF2917CV	85	120	22	1, 1	102	166	20	2600	3200	0, 81
NCF3017CV	85	130	34	1, 1	172	236	30	2400	3000	1, 51
NJG2317VH	85	180	60	3	484	620	76, 5	1400	1800	7, 40
NCF2918CV	90	125	22	1, 1	105	176	20, 8	2400	3000	0, 84
NCF3018CV	90	140	37	1, 5	198	280	35, 5	2200	2800	1, 97
NJG2318VH	90	190	64	3	528	670	81, 5	1400	1800	8, 75
NCF2920CV	100	140	24	1, 1	128	200	24, 5	2200	2600	1, 14
NCF3020CV	100	150	37	1, 5	209	310	37, 5	2000	2600	2, 15
NJG2320VH	100	215	73	3	682	865	104	1200	1500	13, 0
NCF2922CV	110	150	24	1, 1	134	220	26	1900	2400	1, 23
NCF3022CV	110	170	45	2	275	400	47, 5	1800	2200	3, 50
NJG2322VH	110	240	80	3	858	1060	122	1100	1300	17, 5
NCF2924CV	120	165	27	1, 1	172	290	34, 5	1800	2200	1, 73
NCF3024CV	120	180	46	2	292	440	52	1700	2000	3, 80
NCF2224V	120	215	58	2, 1	512	735	85	1400	1700	9, 05
NJG2324VH	120	260	86	3	952	1250	140	1000	1200	22, 5
NCF2926CV	130	180	30	1, 5	205	360	40, 5	1600	2000	2, 33
NCF3026CV	130	200	52	2	413	620	72	1500	1900	5, 80
NJG2326VH	130	280	93	4	1080	1430	156	950	1200	28, 0
NCF2928CV	140	190	30	1, 5	220	390	43	1500	1900	2, 42
NCF3028CV	140	210	53	2	440	680	78	1400	1800	6, 10
NCF2228V	140	250	68	3	693	1020	114	1200	1500	14, 5
NJG2328VH	140	300	102	4	1210	1600	173	850	1100	35, 5
NCF2930CV	150	210	36	2	292	490	55	1400	1700	3, 77
NCF3030CV	150	225	56	2, 1	457	710	80	1300	1600	7, 50
NCF2230V	150	270	73	3	792	1180	132	1100	1400	18, 4
NJG2330VH	150	320	108	4	1450	1930	196	800	1000	42, 5
NCF3032CV	160	240	60	2, 1	512	800	90	1200	1500	9, 10
NCF2232V	160	290	80	3	990	1500	160	950	1200	23, 0

NCF2934CV	170	230	36	2	314	560	60	1200	1500	4,30
NCF3034CV	170	260	67	2,1	671	1060	118	1100	1400	12,5
NCF2234V	170	310	86	4	1100	1700	176	900	1100	28,7
NJG2334VH	170	360	120	4	1760	2450	236	700	900	59,5
NCF2936CV	180	250	42	2	391	695	75	1100	1400	6,20
NCF3036CV	180	280	74	2,1	781	1250	134	1100	1300	16,5
NJG2336VH	180	380	126	4	1870	2650	255	670	800	69,5
NCF2938CV	190	260	42	2	440	780	81,5	1100	1400	6,50
NCF3038CV	190	290	75	2,1	792	1290	140	1000	1300	17,0
NCF2238V	190	340	92	4	1250	1900	196	800	1000	35,7
NJG2338VH	190	400	132	5	2160	3000	280	630	800	80,0
NCF1840V	200	250	24	1,5	176	335	32,5	1100	1400	2,60
NCF2940CV	200	280	48	2,1	528	965	100	1000	1300	9,10
NCF3040CV	200	310	82	2,1	913	1530	160	950	1200	22,5
NJG2340VH	200	420	138	5	2290	3200	290	600	750	92,0
NCF1844V	220	270	24	1,5	183	365	34,5	1000	1200	2,85
NCF2944CV	220	300	48	2,1	550	1060	106	950	1200	9,90
NCF3044CV	220	340	90	3	1080	1800	186	850	1100	29,5
NCF2244V	220	400	108	4	1830	2750	255	700	850	58,0
NJG2344VH	220	460	145	5	2550	3550	320	530	670	111
NCF1848V	240	300	28	2	260	510	47,5	900	1100	4,40
NCF2948CV	240	320	48	2,1	583	1140	114	850	1100	10,6
NCF3048CV	240	360	92	3	1140	1960	200	800	1000	32,0
NJG2348VH	240	500	155	5	2810	3900	345	500	630	147
NCF1852V	260	320	28	2	270	550	50	800	1000	4,75
NCF2952CV	260	360	60	2,1	737	1430	143	750	950	18,5
NCF3052CV	260	400	104	4	1540	2550	250	700	900	46,5
NJG2352VH	260	540	165	6	3410	4800	415	430	530	177
NCF2956CV	280	380	60	2,1	880	1730	166	700	900	19,7
NCF3056CV	280	420	106	4	1570	2650	260	670	850	50,0
NCF1860V	300	380	38	2,1	418	850	75	670	850	10,0

NCF2960CV	300	420	72	3	1120	2200	208	670	800	31, 2
NCF3060CV	300	460	118	4	1900	3250	300	600	750	69, 0
NCF1864V	320	400	38	2, 1	440	900	80	630	800	10, 5
NCF2964CV	320	440	72	3	1140	2360	220	600	750	32, 9
NCF3064CV	320	480	121	4	1980	3450	310	560	700	74, 5
NCF1868V	340	420	38	2, 1	446	950	83	600	750	11, 0
NCF2968CV	340	460	72	3	1190	2500	228	560	700	35, 0
NCF3068CV	340	520	133	5	2380	4150	355	530	670	100
NCF1872V	360	440	38	2, 1	402	900	76, 5	560	700	11, 5
NCF2972CV	360	480	72	3	1230	2600	240	530	670	36, 5
NCF3072CV	360	540	134	5	2420	4300	365	500	630	105
NCF1876V	380	480	46	2, 1	627	1290	114	530	670	19, 5
NCF2976CV	380	520	82	4	1570	3250	300	500	630	52, 5
NCF3076CV	380	560	135	5	2510	4550	380	480	600	110
NCF1880V	400	500	46	2, 1	627	1340	118	500	630	20, 5
NCF2980CV	400	540	82	4	1650	3450	310	480	600	54, 5
NCF3080CV	400	600	148	5	2970	5500	450	450	560	145
NCF1884V	420	520	46	2, 1	660	1430	122	480	600	21, 0
NCF2984CV	420	560	82	4	1650	3600	315	450	560	57, 0
NCF3084CV	420	620	150	5	3030	5700	455	430	530	150
NCF1888V	440	540	46	2, 1	671	1460	125	450	560	22, 0
NCF2888V	440	540	60	2, 1	1060	2700	232	450	560	29, 0
NCF2988V	440	600	95	4	2010	4400	380	430	530	80, 5
NCF3088CV	440	650	157	6	3580	6550	520	400	500	175
NCF2892V	460	580	72	3	1300	3050	260	430	530	44, 0
NCF2992V	460	620	95	4	2050	4500	390	400	500	83, 5
NCF3092CV	460	680	163	6	3690	6950	540	380	480	195
NCF1896V	480	600	56	3	935	2040	170	400	500	35, 5
NCF2896V	480	600	72	3	1320	3150	265	400	500	46, 0
NCF2996V	480	650	100	5	2290	4900	405	380	480	98, 0
NCF3096CV	480	700	165	6	3740	7200	550	360	450	205

NCF18/500V	500	620	56	3	952	2120	173	380	480	36,5
NCF28/500V	500	620	72	3	1340	3350	275	380	480	48,0
NCF29/500V	500	670	100	5	2330	5000	415	380	450	100
NCF30/500CV	500	720	167	6	3800	7500	570	360	450	215
NCF18/530V	530	650	56	3	990	2240	180	360	450	38,5
NCF28/530V	530	650	72	3	1400	3450	285	360	450	49,5
NCF29/530V	530	710	106	5	2640	6100	480	340	430	120
NCF30/530V	530	780	185	6	5230	10600	780	320	400	300
NCF18/560V	560	680	56	3	1020	2360	186	340	430	40,5
NCF28/560V	560	680	72	3	1420	3650	300	340	430	54,0
NCF29/560V	560	750	112	5	3080	6700	500	320	400	140
NCF30/560V	560	820	195	6	5830	11800	865	300	380	345
NCF18/600V	600	730	60	3	1050	2550	196	320	400	51,5
NCF28/600V	600	730	78	3	1570	4300	340	320	400	67,5
NCF29/600V	600	800	118	5	3190	7100	520	300	380	170
NCF18/630V	630	780	69	4	1250	2900	232	300	360	72,5
NCF28/630V	630	780	88	4	1870	5000	390	300	360	92,5
NCF29/630V	630	850	128	6	3740	8650	610	280	340	205
NCF18/670V	670	820	69	4	1300	3150	245	280	340	76,5
NCF28/670V	670	820	88	4	1940	5300	415	280	340	97,5
NCF29/670V	670	900	136	6	3910	9000	630	260	320	245
NCF28/710V	710	870	95	4	2330	6300	480	260	320	115
NCF29/710V	710	950	140	6	4290	10000	695	240	300	275
NCF18/750V	750	920	78	5	1870	4500	335	240	300	110
NCF28/750V	750	920	100	5	2640	6950	520	240	300	140
NCF29/750V	750	1000	145	6	4460	10600	710	220	280	315
NCF18/800V	800	980	82	5	1940	4800	345	220	280	130
NCF28/800V	800	980	106	5	2750	7500	550	220	280	165
NCF29/800V	800	1060	150	6	4950	12200	800	200	260	360
NCF18/850V	850	1030	82	5	2010	5100	365	200	260	135
NCF28/850V	850	1030	106	5	2860	8000	570	200	260	175

NCF29/850V	850	1120	155	6	5230	12700	830	190	240	405
NCF18/900V	900	1090	85	5	2380	6000	425	190	240	160
NCF28/900V	900	1090	112	5	3190	9150	655	190	240	208
NCF29/900V	900	1180	165	6	5940	14600	950	170	220	472
NCF18/950V	950	1150	90	5	2420	6300	440	170	220	185
NCF28/950V	950	1150	118	5	3410	9800	655	170	220	240
NCF29/950V	950	1250	175	7, 5	6600	16300	1020	160	200	565
NCF18/1000V	1000	1220	100	6	2920	7500	455	160	200	230
NCF28/1000V	1000	1220	128	6	4130	11600	720	160	200	310
NCF29/1000V	1000	1320	185	7, 5	7480	18600	1160	150	190	680
NCF18/1120V	1120	1360	106	6	3740	9650	585	130	170	298