

Model	Size (mm)				Basic load ratings (N)		Fatigue limit load (N)	Limit speed (r/min)	Parameters of speed (r/min)	Weight
	d	D	B(or)T	Rmin	Cr	Cor	Cur	Ng	Nb	(kg)
22315EJA/VA405	75	160	55	2.1	439000	474000	—	4300	3200	5.55
22316EJA/VA405	80	170	58	2.1	489000	539000	—	4000	3000	6.6
22317EJA/VA405	85	180	60	3	549000	619000	—	3800	2800	7.65
22317EJA/VA406	85	180	60	3	549000	619000	—	3800	2800	7.65
22318EJA/VA405	90	190	64	3	609000	694000	—	3600	2600	9.05
22319EJA/VA405	95	200	67	3	669000	764000	—	3400	2600	10.5
22320EJA/VA405	100	215	73	3	814000	949000	—	3000	2400	13.5
22320EJA/VA406	100	215	73	3	814000	949000	—	3000	2400	13.5
22322EJA/VA405	110	240	80	3	949000	1119000	—	2800	2000	18.4
22322EJA/VA406	110	240	80	3	949000	1119000	—	2800	2000	18.4
22324CCJA/W33VA405	120	260	86	3	964000	1119000	—	2600	2000	23
22324CCJA/W33VA406	120	260	86	3	964000	1119000	—	2600	2000	23
22326CCJA/W33VA405	130	280	93	4	1119000	1319000	—	2400	1800	29
22326CCJA/W33VA406	130	280	93	4	1119000	1319000	—	2400	1800	29
22328CCJA/W33VA405	140	300	102	4	1289000	1559000	—	2200	1700	36.5
22328CCJA/W33VA406	140	300	102	4	1289000	1559000	—	2200	1700	36.5
22330CCJA/W33VA405	150	320	108	4	1459000	1759000	—	2000	1600	43.5
22330CCJA/W33VA406	150	320	108	4	1459000	1759000	—	2000	1600	43.5
22332CCJA/W33VA405	160	340	114	4	1599000	1959000	—	1900	1500	52
22332CCJA/W33VA406	160	340	114	4	1599000	1959000	—	1900	1500	52
22334CCJA/W33VA405	170	360	120	4	1759000	2159000	—	1800	1400	61
22334CCJA/W33VA406	170	360	120	4	1759000	2159000	—	1800	1400	61
22336CCJA/W33VA405	180	380	126	4	1999000	2449000	—	1700	1300	71.5
22336CCJA/W33VA406	180	380	126	4	1999000	2449000	—	1700	1300	71.5
22338CCJA/W33VA405	190	400	132	5	2119000	2649000	—	1600	1200	82.5
22338CCJA/W33VA406	190	400	132	5	2119000	2649000	—	1600	1200	82.5
22340CCJA/W33VA405	200	420	138	5	2319000	2899000	—	1500	1200	95
22340CCJA/W33VA406	200	420	138	5	2319000	2899000	—	1500	1200	95
22344CCJA/W33VA405	220	460	145	5	2699000	3449000	—	1400	1000	120
22348CCJA/W33VA405	240	500	155	5	3099000	3999000	—	1300	950	155

22308E/VA405	40	90	33	1.5	149000	139000	—	8000	6000	1.1
22309E/VA405	45	100	36	1.5	182000	182000	—	7000	5300	1.4
22310E/VA405	50	110	40	2	219000	223000	—	6300	4800	1.9
22311E/VA405	55	120	43	2	269000	279000	—	5600	4300	2.45
22312E/VA405	60	130	46	2.1	309000	334000	—	5300	4000	3.1
22313E/VA405	65	140	48	2.1	339000	359000	—	5000	3800	3.75
22314E/VA405	70	150	51	2.1	399000	429000	—	4500	3400	4.55