

Model	Size (mm)				Basic load ratings (N)		Fatigue limit load (N)	Limit speed (r/min)	Parameters of speed (r/min)	Weight
	d	D	B(or)T	Rmin	Cr	Cor	Cur	Ng	Nb	(kg)
BS2-2208-2CS	40	80	28	1.1	95500	89000	—	2200	—	0.57
BS2-2308-2CS	40	90	38	1.5	149000	139000	—	1900	—	1.2
BS2-2209-2CS	45	85	28	1.1	101000	97000	—	2000	—	0.66
BS2-2210-2CS	50	90	28	1.1	103000	107000	—	1900	—	0.7
BS2-2211-2CS	55	100	31	1.5	124000	126000	—	1700	—	1
BS2-2311-2CS	55	120	49	2	269000	279000	—	1400	—	2.8
BS2-2212-2CS	60	110	34	1.5	155000	165000	—	1600	—	1.3
BS2-2213-2CS	65	120	38	1.5	192000	215000	—	1500	—	1.6
BS2-2214-2CS	70	125	38	1.5	207000	227000	—	1400	—	1.8
BS2-2215-2CS	75	130	38	1.5	211000	239000	—	1300	—	2.1
BS2-2315-2CS	75	160	64	2.1	439000	474000	—	950	—	6.5
BS2-2216-2CS	80	140	40	2	235000	269000	—	1200	—	2.4
BS2-2217-2CS	85	150	44	2	284000	324000	—	1100	—	3
BS2-2218-2CS	90	160	48	2	324000	374000	—	1000	—	3.7
BS2-2220-2CS	100	180	55	2.1	424000	489000	—	900	—	5.5
BS2-2222-2CS5/VT143	110	200	63	2.1	559000	639000	—	800	—	7.6
BS2-2224-2CS	120	215	69	2.1	629000	764000	—	750	—	9.75
BS2-2224-2CS	120	215	69	2.1	629000	764000	—	750	—	9.75
24013-2CS5/VT143	65	100	35	1.1	131000	172000	—	1000	—	0.95
24015-2CS2/VT143	75	115	40	1.1	172000	231000	—	950	—	1.55
24020-2CS2/VT143	100	150	50	1.5	284000	414000	—	800	—	3.15
23120-2CS2/VT143	100	165	52	2	364000	489000	—	850	—	4.55
23220-2CS	100	180	60.3	2.1	474000	599000	—	700	—	6.85
23022-2CS	110	170	45	2	309000	439000	—	900	—	3.75
23122-2CS2/VT143	110	180	56	2	429000	584000	—	800	—	5.55
24122-2CS2/VT143	110	180	69	2	519000	749000	—	630	—	6.85
23024-2CS2/VT143	120	180	46	2	354000	509000	—	850	—	4.2
24024-2CS2/VT143	120	180	60	2	429000	669000	—	670	—	5.45
24124-2CS2/VT143	120	200	80	2	654000	949000	—	560	—	10.5

23026-2CS2/VT143	130	200	52	2	429000	609000	—	800	—	6
24026-2CS2/VT143	130	200	69	2	539000	814000	—	600	—	8.05
24126-2CS2/VT143	130	210	80	2	679000	999000	—	530	—	11
24028-2CS2/VT143	140	210	69	2	569000	899000	—	560	—	8.55
24128-2CS2/VT143	140	225	85	2.1	764000	1159000	—	450	—	13.5
24024-2CS2/VT143	120	180	60	2	429000	669000	—	670	—	5.45
24124-2CS2/VT143	120	200	80	2	654000	949000	—	560	—	10.5
23026-2CS2/VT143	130	200	52	2	429000	609000	—	800	—	6
24026-2CS2/VT143	130	200	69	2	539000	814000	—	600	—	8.05
24126-2CS2/VT143	130	210	80	2	679000	999000	—	530	—	11
24028-2CS2/VT143	140	210	69	2	569000	899000	—	560	—	8.55
24128-2CS2/VT143	140	225	85	2.1	764000	1159000	—	450	—	13.5
23228-2CS5/VT143	140	250	88	3	914000	1249000	—	530	—	19.5
24030-2CS2/VT143	150	225	75	2.1	654000	1039000	—	530	—	10.5
24130-2CS2/VT143	150	250	100	2.1	1019000	1529000	—	400	—	20
24032-2CS2/VT143	160	240	80	2.1	749000	1199000	—	450	—	13
23132-2CS2/VT143	160	270	86	2.1	979000	1369000	—	530	—	20.5
24034-2CS2/VT143	170	260	90	2.1	929000	1459000	—	400	—	17.5
24134-2CS2/VT143	170	280	109	2.1	1219000	1859000	—	360	—	27.5
24036-2CS2/VT143	180	280	100	2.1	1079000	1729000	—	380	—	23
24138-2CS2/VT143	190	320	128	3	1599000	2499000	—	340	—	43
24140-2CS	200	340	140	3	1799000	2799000	—	320	—	53.5
23240-2CS2/VT143	200	360	128	4	1859000	2699000	—	430	—	58
23944-2CS	220	300	60	2.1	545000	1079000	—	600	—	12.5